

IEC-725

20-slot Industrial 19" Rackmount Chassis

" PCI/ISA or ISA backplane and 300 Watt Power Supply "



Specifications

- **Construction** : heavy-duty steel.
- **Cooling & Filter** : 3 cooling fans with removable air filter
- **Disk Drive Housing** : 3x 3½", or 1x 5¼" and 3 x 3½" (IEC-725C)
- **Indicators** : LEDs power ON/OFF, HDD
- **Switches** : KB lock, Reset & power ON/OFF.

- **Keyboard Connector** : standard DIN connectors on front and rear panel.
- **Size** : 438(W) x 615(D) x 177 (H) mm.
- **Weight** : 23 Kg
- **Backplanes**

PBI-20S/D/Q	20 ISA (single, dual or quad)
PBPI-19S	13 ISA, 4 PCI, 2 PICMG (single)
PBPI-18SD	3 ISA, 4 PCI, 2 PICMG (x 2)
PBPI-17SQ	1 ISA, 2(3) PCI, 1 PICMG (x 4)

POWER SUPPLY

- **Output rating** : 300 W (max.)
- **Input Voltage** : 90 to 132 V_{AC} or 180 to 264 V
- **Input Frequency** : 47~63 Hz
- **Output** : +5V @ 36 A, +12 V @ 16 A, -5 V @ 0.5 A, -12 V @ 0.5 A
- **MTBF** : 100,000 hours at 25°C
- **Safety** : UL/CSA/TÜV/CE/FCC appr.
- **Option** : Redundant PS (IEC-725C)

ENVIRONMENTAL

- **Operating Temperature**: 0 to + 55 °C.
- **Relative Humidity**: 10 to 95%

Ordering

- ☐ **IEC-725**: Industrial 19" Rackmount Chassis, 4x 3½" drives, 20-slot ISA and 300 W PS/2 power supply
- ☐ **IEC-725C**: Industrial 19" Rackmount Chassis, 1x 5¼" + 3x 3½" drives, 20-slot ISA, 2x 300 W redundant power supply

