

IEC-740A

Full-size, 6-slot Wallmount Chassis "PISA or ISA-based with 150 W Power Supply"



PASSIVE BACKPLANES

PBI-6S	6 ISA (full-size cards)
PBPI-5S	2 ISA, 2 PCI, 1 PICMG
PBP-5S	3 PCI, 3 PISA

ENVIRONMENTAL

- **Operating Temperature:** 0 to 50°C
- **Relative Humidity:** 10 to 95%
- **Vibration (operating):** 5 to 17 Hz, 0.1" double-amplitude displacement; 17 to 500 Hz, 1.5 G acceleration peak to peak
- **Shock (operating):** 10 G acceleration peak (11 ms duration)
- **EMI:** meets FCC/VDE Class A

Ordering

- **IEC-740A:** Full-size Wallmount Chassis with 6-slot ISA backplane and 150 W power supply
PCI/ISA or PISA backplane optional

Specifications

- **Construction :** heavy-duty steel
- **Disk Drive Capacity :** one 3½" FDD and one 3½" HDD
- **LEDs:** power On/Off, HDD on front
- **Controls:** reset on front panel
- **Cooling Fan:** one 49 CFM cooling fan on front panel with air filter
- **Dimensions:** 170 (W) x 192 (H) x 393 (D) mm
- **Weight:** 12.3 lbs (5.6 kg)

POWER SUPPLY

- **Output Rating :** 150 W (max.)
- **Input Voltage :** 90 to 132 V_{AC} or 180 to 264 V
- **Input Frequency :** 47~63 Hz
- **Output:** +5 V @ 15 A, -5 V @ 1 A +12 V @ 5 A, -12 V @ 1 A (max.)
- **MTBF:** > 50,000 hours at 70% load
- **Safety :** UL/CSA/TÜV/CE/FCC approved.
- **EMI :** Meets FCC/VDE Class A

